

NPS-53-89-001

NAVAL POSTGRADUATE SCHOOL

Monterey, California



SOLUTION OF LINEAR INITIAL VALUE
PROBLEMS ON A HYPERCUBE

Beny Neta

November 1988

Approved for public release; distribution unlimited
Prepared for: Texas Tech University
Lubbock, TX 79409

FedDocs
D 208.14/2
NPS-53-89-001

001
NAVAL POSTGRADUATE SCHOOL
MONTEREY, CALIFORNIA

Rear Admiral R. C. Austin
Superintendent

Harrison Shull
Provost

This report was prepared in conjunction with research conducted for the National Science Foundation and funded through Texas Tech University. Reproduction of all or part of this report is authorized.

Prepared by:

0 0 1

REPORT DOCUMENTATION PAGE

DUDLEY KNOX LIBRARY
NAVAL POSTGRADUATE SCHOOL
MONTEREY CA 93943-5101

1a SECURITY CLASSIFICATION		1b RESTRICTIVE MARKINGS	
2a SECURITY CLASSIFICATION AUTHORITY		3 DISTRIBUTION/AVAILABILITY OF REPORT	
4a CLASSIFICATION/DOWNGRADING SCHEDULE		Approved for public release; distribution unlimited	
5a PERFORMING ORGANIZATION REPORT NUMBER(S) NPS-53-89-001		5b MONITORING ORGANIZATION REPORT NUMBER(S) NPS-53-89-001	
6a NAME OF PERFORMING ORGANIZATION Postgraduate School	6b OFFICE SYMBOL (If applicable) 53	7a NAME OF MONITORING ORGANIZATION National Science Foundation	
8a ADDRESS (City, State, and ZIP Code) Monterey, CA 93943		8b ADDRESS (City, State, and ZIP Code) Washington, D.C. 20550	
9a NAME OF FUNDING/SPONSORING ORGANIZATION Texas Technical University	9b OFFICE SYMBOL (If applicable)	9 PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER	
10a ADDRESS (City, State, and ZIP Code) Fort Worth, TX 79409		10 SOURCE OF FUNDING NUMBERS	
		PROGRAM ELEMENT NO	PROJECT NO
		TASK NO	WORK UNIT ACCESSION NO
11 SUMMARY (Include Security Classification) Solution of Linear Initial Value Problems on a Hypercube			
12 PERSONAL AUTHOR(S) Beny Neta and C. P. Katti			
13a TYPE OF REPORT Technical Report	13b TIME COVERED FROM 8/1/86 TO 9/30/88	14 DATE OF REPORT (Year, Month, Day) 1 November 1988	15 PAGE COUNT 12
16 SUPPLEMENTARY NOTATION			
17 COSATI CODES		18 SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
17a	17b	17c	
GROUP	SUB-GROUP		
		initial value problems, parallel scheme, hypercube, box scheme, recursive doubling technique	
19 ABSTRACT (Continue on reverse if necessary and identify by block number)			
There are many articles discussing the solution of boundary value problems on various parallel machines. The solution of initial value problems does not lend itself to parallelism, since in this case one uses methods that are sequential in nature. We develop a parallel scheme for initial value problems based on the box scheme and a modified recursive doubling technique. Explicit Runge Kutta methods were discussed by Jackson and Norsett (1986) and Lie (1987). Lie assumes that each processor of the parallel computer having vector capabilities.			
20 DISTRIBUTION/AVAILABILITY OF ABSTRACT UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT <input type="checkbox"/> DTIC USERS		21 ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED	
22a NAME OF RESPONSIBLE INDIVIDUAL Beny Neta		22b TELEPHONE (Include Area Code) (408) 646-2235	22c OFFICE SYMBOL 53Nd

SOLUTION OF LINEAR INITIAL VALUE PROBLEMS ON A HYPERCUBE

C. P. Katti
Jawaharlal Nehru University
School of Computer and Systems Sciences
New Delhi, 110067
India

and

B. Neta
Naval Postgraduate School
Department of Mathematics
Code 53Nd
Monterey, CA 94943

Abstract

There are many articles discussing the solution of boundary value problems on various parallel machines. The solution of initial value problems does not lend itself to parallelism, since in this case one uses methods that are sequential in nature.

Here we develop a parallel scheme for initial value problems based on the box scheme and a modified recursive doubling technique.

Fully implicit Runge Kutta methods were discussed by Jackson and Norsett (1986) and Lie (1987). Lie assumes that each processor of the parallel computer having vector capabilities.

1 Introduction

We consider the solution of linear initial value problems on a hypercube. "By a hypercube we intend a distributed memory MIMD computer with communication between processors ... via a communication network having the topology of a p -dimensional cube, with the vertices considered as processors and the edges as communication links" (Keller and Nelson, 1987). See also Fox (1984, 1985,

1987) and Fox and Otto (1984). Our method of solution is based on the box scheme to discretize the system of initial value problems

$$y' = Ay + f(x)$$

$$y(a) = y'_0$$

where y and f are n -dimensional vectors and A is an $n \times n$ matrix. The resulting system of equations is solved by a modified version of the recursive doubling technique (see Stone, 1973).

In the next section, the discretization is described and the resulting system of equation is given. Section 3 will describe the modified recursive doubling technique and its application to our system.

It will be interesting to experiment with the method and compare the results to a sequential initial value solver of the same order.

2 The Single Step Method

Consider the system of initial value problems

$$\begin{aligned} y' &= A(x)y + f(x), & a \leq x \leq b \\ y(a) &= y'_0 \end{aligned} \tag{1}$$

where

$$\begin{aligned} y &= (y_1, \dots, y_n)^T, & f &= (f_1(x), \dots, f_n(x))^T, \\ y'_0 &= (y'_{10}, \dots, y'_{n0}), \end{aligned}$$

and

$$A = a_{ij}(x), \quad 1 \leq i, j \leq n.$$

Let

$$x_j = a + jh, \quad j = 0, 1, \dots, m \tag{2}$$

where

$$h = \frac{b - a}{m} \tag{3}$$

be a uniform mesh. The box scheme (see e.g. Keller, 1976), applied to (1) yields

$$\begin{aligned} y_{j+1} &= y_j + h \left\{ A_{j+\frac{1}{2}} (y_{j+1} + y_j) / 2 + f_{j+\frac{1}{2}} \right\}, \\ y_0 &= y'_0 \end{aligned} \quad (4)$$

where

$$\begin{aligned} A_{j+\frac{1}{2}} &= A \left(a + \left(j + \frac{1}{2} \right) h \right) \\ f_{j+\frac{1}{2}} &= f \left(a + \left(j + \frac{1}{2} \right) h \right) \end{aligned}$$

and y_j is the approximation to $y(x_j)$.

Let $\{j_i, i = 1, 2, \dots, s\}$ be a strictly increasing sequence such that $j_1 > 0$ and $j_s = m$. We shall compute the solution at the points $x_i = x_{j_i}$. Let Φ_i be $n \times n$ matrices defined for each i

$$\Phi_i = \prod_{j=j_{i-1}}^{j_i-1} \left(I - \frac{h}{2} A_{j+\frac{1}{2}} \right)^{-1} \left(I + \frac{h}{2} A_{j+\frac{1}{2}} \right), \quad i = 1, 2, \dots, s, \quad (5)$$

where $j_0 = 0$ and h is sufficiently small so that $I - \frac{h}{2} A_{j+\frac{1}{2}}$ are nonsingular.

Similarly let the n -vector φ_i be

$$\begin{aligned} \varphi_i &= \left(I - \frac{h}{2} A_{j_i-\frac{1}{2}} \right)^{-1} \left(I + \frac{h}{2} A_{j_i-\frac{1}{2}} \right) \tilde{y}_{j_i-1-j_{i-1}} \\ &\quad + h \left(I - \frac{h}{2} A_{j_i-\frac{1}{2}} \right)^{-1} f_{j_i-\frac{1}{2}}, \quad i = 1, 2, \dots, s, \end{aligned} \quad (6)$$

where

$$\tilde{y}_0 = 0 \quad (7)$$

and

$$\tilde{y}_{j+1} = \left(I - \frac{h}{2} A_{j+\frac{1}{2}+j_{i-1}} \right)^{-1} \left[\left(I + \frac{h}{2} A_{j+\frac{1}{2}+j_{i-1}} \right) \tilde{y}_j + h f_{j+\frac{1}{2}+j_{i-1}} \right] \quad (8)$$

$$j = 0, \dots, j_i - j_{i-1} - 2.$$

Then it can be easily shown as in Keller and Nelson (1987), that

$$Y_{j_i} = \Phi_i y_{j_{i-1}} + \varphi_i, \quad i = 1, 2, \dots, s. \quad (9)$$

Remarks

1. The matrices to be inverted are of order n , the number of equations in the original system (1).
2. The last factor in the product defining Φ_i is the matrix required in computing φ_i .
3. The vector $\tilde{y}_{j_i-1-j_{i-1}}$ can be computed by (7) - (8) in the same loop one computes Φ_i since it requires the same matrices.

3 Parallel Evaluation

To solve (9) on a hypercube with $p = s$ processors, one can modify the recursive doubling technique developed by Stone (1973).

Let

$$\begin{aligned} b_1 &= \Phi_1 y'_0 + \varphi_1 \\ b_j &= \varphi_j, \quad j = 2, 3, \dots, s \end{aligned} \tag{10}$$

and let $Y_i(j)$ be a function of $b_j, b_{j-1}, \dots, b_{j-i+1}, \Phi_j, \dots, \Phi_{j-i+1}$. Then the following results can be proved using similar arguments as in Stone(1973).

Theorem. Let $Y_i(j)$ satisfy the recurrence relation

$$Y_{i+1}(j) = Y_1(j) + \Phi_j Y_i(j-1), \quad i, j \geq 1 \tag{11}$$

with boundary conditions

$$\begin{aligned} Y_1(j) &= b_j, \quad j \geq 1 \\ Y_i(j) &= 0, \quad j \leq 0 \text{ or } i \leq 0. \end{aligned} \tag{12}$$

Then

(i)

$$Y_{i+s}(j) = Y_s(j) + \prod_{k=j-s+1}^j \Phi_{2j-k-s+1} Y_i(j-s) \tag{13}$$

(ii)

$$Y_i(j) = \sum_{k=1}^j \left\{ \prod_{s=k+1}^j \Phi_{j-s+k+1} \right\} Y_1(k), \quad i \geq j \geq 1, \quad (14)$$

(iii) for

$$i \geq j \geq 1, \quad Y_i(j) = y_{ji}. \quad (15)$$

Corollary

$$Y_{2i}(j) = Y_i(j) + \left\{ \prod_{k=j-i+1}^j \Phi_{2j-k-i+1} \right\} Y_i(j-i), \quad i, j \geq 1 \quad (16)$$

This corollary provides the recursive doubling algorithm for the solution of (9). Let

$$M_i(j) = \begin{cases} \prod_{k=1}^j \Phi_{j-k+1} & j \leq i \\ \prod_{k=j-i+1}^j \Phi_{2j-k+1-i}, & j \geq i \end{cases} \quad (17)$$

then (16) can be written as

$$\begin{aligned} Y_{2i}(j) &= Y_i(j) + M_i(j)Y_i(j-i) \quad i, j \geq 1 \\ M_{2i}(j) &= M_i(j)M_i(j-i) \quad i, j \geq 1 \end{aligned} \quad (18)$$

with boundary conditions

$$\begin{aligned} M_1(j) &= \Phi_j, \quad j \geq 1 \\ M_1(j) &= I, \quad i \leq 0 \text{ or } j \leq 0. \end{aligned} \quad (19)$$

We are now ready to state the algorithm.

Algorithm

For $i = 1$ to $s/2$ in steps of i do:

$$\begin{aligned} Y_{2i}(j) &= Y_i(j) + M_i(j)Y_i(j-i) \quad i \leq j \leq s \\ M_{2i}(j) &= M_i(j)M_i(j-i) \quad i \leq j \leq s \end{aligned}$$

Next i .

From our theorem, $Y_s(j) = y_{j_s}$ for $1 \leq j \leq s$, so that Ys is the solution of (9). We note that for each i , the indices pertaining to j are executed simultaneously on s processors. Since i doubles during each iteration, $\log_2 s$ iterations are required for computation.

Acknowledgements

This work was partially supported by the National Science Foundation, through Grants No. INT-8519159 and INT-8613396.

References

1. H.B. Keller and P. Nelson (1987). *Hypercube Implementations of Parallel Shooting*, **Applied Mathematics and Computations**, to appear.
2. G. Fox (1984). *Concurrent Processing for Scientific Calculations*, Proceedings COMPCON 1984 Conference. pp.70-73, IEEE Computer Society.
3. G.C. Fox (1984). *Are Concurrent Processors General Purpose Computers?*, **IEEE Trans. Nucl. Sci.** NS-32, pp.182-186.
4. G.C. Fox and S. W. Otto (1984). *Algorithm for Concurrent Processors*, **Physics Today**, 37, No. 5, pp.50-59.
5. H.S. Stone (1973). *An Efficient Parallel Algorithm for the Solution of a Tridiagonal Linear System of Equations*, **J. Assoc. Comput. Mach.**, 20, pp. 27-38.
6. H. B. Keller (1976). *Numerical Solution of Two Point Boundary Value Problems*, **SIAM, Reg. Conf. Ser. in Applied Math.**
7. K. K. Jackson and S. P. Norsett (1986). *Parallel Runge-Kutta Methods*, unpublished report.

8. I. Lie (1987). *Some Aspects of Parallel Runge-Kutta Methods*, Institutt for Numerisk Matematikk, Universitetet i Trondheim, Norway, ISBN 82-7151-068-1, 39 pages.

DISTRIBUTION LIST

	NO. OF COPIES
Director Defense Tech. Information Center Cameron Station Alexandria, VA 22314	2
Director of Research Administration Code 012 Naval Postgraduate School Monterey, CA 93943	1
Library Code 0142 Naval Postgraduate School Monterey, CA 93943	2
Department of Mathematics Code 53 Naval Postgraduate School Monterey, CA 93943	1
Center for Naval Analyses 4401 Ford Avenue Alexandria, VA 22302-0268	1
Professor Beny Neta Code 53Nd Department of Mathematics Naval Postgraduate School Monterey, CA 93943	15
Dr. C. P. Katti J. Nehru University School of Computer & Systems Sciences New Delhi 110067 India	5
Professor Paul Nelson Texas A & M University Department of Nuclear Engineering and Mathematics College Station, TX 77843-3133	1
Professor H. B. Keller Department of Applied Mathematics California Institute of Technology Pasadena, CA 91125	1

Professor H. Dean Victory, Jr. Texas Tech University Department of Mathematics Lubbock, TX 79409	1
Professor Gordon Latta Code 53Lz Department of Mathematics Naval Postgraduate School Monterey, CA 93943	1
Professor Allan Goldstein Code 53Go Department of Mathematics Naval Postgraduate School Monterey, CA 93943	1
Professor Arthur Schoenstadt Code 53Zh Department of Mathematics Naval Postgraduate School Monterey, CA 93943	1
Professor M. M. Chawla, Head Department of Mathematics III/III/B-1, IIT Campus Hauz Khas, New Delhi 110016 India	1

DUDLEY KNOX LIBRARY



3 2768 00341737 9